



28 Derrykerrib Road, Newtownbutler,
Fermanagh, BT928GB.
Tel. +44 2867737177
sales@fbbarriers.co.uk
www.fbbarriers.co.uk

DATA SHEET

Finnbarr Fire Barrier:

FB 60-15 SuperLite

Description

The **FB 60-15 SuperLite** is symmetrical composite of treated, woven glass fabrics, needled glass fibres and aluminium foils. This fire barrier is lightweight, flexible and easily cut to size and is used to provide compartmentation in concealed cavities and spaces in building such as lofts and above suspended ceilings. FB 60-15 SuperLite will provide 60 minutes integrity and 15 minutes insulation when installed according to the fitting instructions which can be found on the back of each product label or downloaded from the website. www.fbbarriers.co.uk

Physical Properties

Colour	White
Odour	None
Nominal Thickness	6.5mm
Nominal Weight	1334 g/m ²
Fibre Diameter	> 6 microns (non respirable)

Fire Tests and Assessments

BS EN 1363-1: 2020
BS EN 1364-1: 2015

Efectis
Report No: EUI-24-B-000732

Dimensions

Length	6m
Width	130 cm
Pack Area & Weight	7.8 m ² nominal; 10.4 kg incl. packaging

Packaging

Concertina folded and wrapped in thick polythene sheet