



28 Derrykerrib Road, Newtownbutler,
Fermanagh, BT928GB.
Tel. +44 2867737177
sales@fbbarriers.co.uk
www.fbbarriers.co.uk

DATA SHEET

Finnbarr Fire Barrier:

FB 60-60 H

Description

The **FB 60-60** is a high-performance, symmetrical composite fire barrier constructed from treated woven glass fabrics, needled glass fibers, and aluminum foils. This flexible and easily customizable fire barrier is designed for use as a ceiling membrane to provide **horizontal** compartmentation in concealed cavities. When installed in accordance with the provided fitting instructions, available on the product label or downloadable from www.fbbarriers.co.uk. It delivers 60 minutes of integrity and 60 minutes of insulation, ensuring robust fire protection.

Physical Properties

Colour	White
Odour	None
Nominal Thickness	18mm
Nominal Weight	4900 g/m ²
Fibre Diameter	> 6 microns (non respirable)

Fire Tests and Assessments

BS 476: Part 22: 1987 Clause 9

Warringtonfire
Report No: 548656/R

Dimensions

Length	6m
Width	130 cm
Pack Area & Weight	7.8 m ² nominal; 40 kg inc. packaging

Packaging

Concertina folded and wrapped in thick polythene sheet